

CALIBER 775 – 7³/₄"



Product Specifications

Analog quartz movement

Line	normtech
Caliber	775
Size	7 ³ / ₄ "
Version Swiss Made	5 Jewels / gold plated EOL
Version Swiss Parts	1 Jewels / nickel plated
Standard battery life	34 months
High battery life	48 months
Standard hand fitting height	1

Functions

- Date
- 3 hands

Features

- Repairable metal watch movement
- Power saving mechanism with pulled out stem:
Reduction of consumption approximately 70%
- Many high hand heights available

CALIBER 775 – 7³/₄"

Technical Specifications

Diameter Total	17.50 mm
Case fitting	17.20 mm
Movement height	2.50 mm
Height over standard battery	2.75 mm
Height over high battery	3.15 mm
Movement rest	0.30 mm
Height over stem	1.00 mm
Length of stem travel	0.90 mm
Stem thread	0.90 mm
Useful torque second – typical	7 µNm
Useful torque minute – typical	350 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Battery Specifications

Standard battery	No. 364
High battery	No. 377
Standard battery life	34 months
High battery life	48 months
Battery voltage	1.5 V
Current consumption – typical	0.83 µA (Date Mechanism not in Gear)
Current consumption – maximum	1.35 µA (Date Mechanism not in Gear)

Watch production

Drawing Casing ring (standard, PDF)
Drawing Casing ring (hohe Batterie, PDF)
Drawing Dial (stem 3h, calendar 3h, PDF)
Drawing Dial (stem 3h, calendar 6h, PDF)
Drawing Dial (stem 3h, calendar 3h, round, PDF)
Drawing Dial (stem 3h, calendar 4h, PDF)
Drawing Dial (stem 3h, calendar 4h, round, PDF)
Drawing Dial (stem 3h, calendar 4h, PDF)
Drawing Hand fitting (hand height 1-5, PDF)
Drawing Hand fitting (hand height 6, PDF)
Drawing Stem

User's manual

User's manual (PDF)

Watch repairs

Technical instruction (PDF)