

ROSADA 103 M-LINE PELLET STOVE



Product data sheet

Product range	Pellet stove
Brand name	Zibro
Model	Rosada 103 M-line
EAN code (no side panels)	8713508765846

Technical specifications

Heater capacity (min - max)*	kW	4.25 - 10.3
Thermal efficiency (nett) nominal/reduced*	%	91.4 / 94.3
Hourly consumption (min - max)	kg/h	0.9 - 2.3
Electrical consumption (ignition - running)	kW	0.3 - 0.1
For rooms up to (max combined volume)*	m ³	270
CO level at 13% O ₂ (nom/reduced)*	%	0.01 / 0.01
Average dust content at 13% O ₂ *	mg/m ³	3
Control		Thermostatic
Power supply	V/Hz	230 / 50
Dimensions unit (w x d x h)	mm	480 x 485 x 1082
Net weight	kg	95
Hopper capacity	kg	17
Exhaust outlet (diameter)	cm	8
Exhaust outlet position		back
Flue gas temperature (nom / reduced)*	°C	129 / 74.3
Flue gas mass flow (nom / reduced)*	g/s	TBD
Intermittent burning system		Yes
Can be used in combined flue system		No
Sound pressure level	dB(A)	TBD
Autonomy (min - max)	h	7.5 - 19
Fuel type: Pellet (diameter)**	mm	6
Guarantee	years	2

* According to EN 14785:2006


** Pellets should comply with CEN / TS 14961 and / or Ö-norm and / or EN+standard

*** For indication only


Accessories

Instructions for use		
	red	8713508764610
Set majolica	black	8713508765280
	white	8713508767215

Remote control	
----------------	--



20 ft = N/A
40 ft = N/A
HQ = N/A



W x D x H =
530 x 530 x 1015 mm



Gross =
104 kg

zibro®

home made climates

ROSADA 103 M-LINE PELLET STOVE



Weektimer



Back exhaust



Remote control



Auto fan



Environmental friendly
(carbon neutral)



Day timer

Features

Ease of operation

Zibro Pellet heaters are easy to operate. The stove is provided with an advanced hot air ignition system which will ignite the heater automatically once the relative button is pressed. The heating capacity of the stove is regulated with a computer feedback system using feedback from an integrated room temperature sensor to achieve the desired room temperature automatically. Once the temperature has reached the desired temperature the heater will automatically reduce its heat output to the lowest possible value, heater will not switch off. The starting time can be programmed with an integrated week timer. This allows the user to enter two starts and stop moments each day of a week. The auger speed can also be set manually; which allows longer burning time when a lower heater output is selected.

Superb innovative design

This Italian designed pellet stove is extremely elegant and has a high capacity and efficiency.

Efficiency

With its objectively tested efficiency of 94.3% the efficiency of this stove is amongst the highest efficiencies available in the market.

Automatic regulating function

An integrated room temperature sensor activates the heater according to the set temperature, using the hot air ignition system to start and switches it back once the desired temperature has been reached. This automatic function can be programmed twice a day for the whole week.

Flame pattern

Zibro Pellet heaters have an attractive flame pattern, and a large window enables you to see the flames, enhancing the cosy atmosphere in the room.

Continuous operation

Because of the large hopper (17 kg) the stove can operate continuously but need to be refilled after maximum 19 hours.

Design

With timeless beauty Rosada M-line is also designed to be easy on the eye - as an elegant addition to your home.

Environmental friendly

The pellets are wood based and derived from natural products; not adding extra CO₂ to the atmosphere (CO₂ neutral).

Convenience

Pellets are easy to use, and they come in handy bags; this fuel offers maximum convenience, while at the same time providing a high efficiency rating and a high degree of environmental compatibility

Ash Pan

The ash pan can hold the ash from more than 600 kg (or 400 hours) of burnt pellets.

Easy maintenance

You can do many of the basic maintenance tasks yourself. However, if professional service is needed, all the stove components are easily accessible so that the pellet stove rarely has to be detached from the chimney. As with any other pellet stove the daily cleaning of the burning pot is very important for optimal performance.

Comfortable to use

Easy, clean and safe. Pellet fuel has a high efficiency rating and is convenient and easy to use.

Optimum price/performance ratio

Anyone who wants a heating source that is both economical and efficient will get their money's worth with a Zibro Pellet heater. Wood pellets have a heat output that is comparable to oil and gas, and are available at very competitive price.

Made in Italy

This heater has been produced in Italy according to the EN 14785:2006 standard.

Safety

Thanks to multiple different alarms, the Zibro stove reacts automatically to abnormal conditions in operation or excess flue pressure with an immediate shutdown.

Heat exchanger

A high efficiency is achieved due to the highly sophisticated heat exchanger in combination with modern software control technologies which use most of the hot air before it leaves the flue.

Remote control

With the easy to use remote control the stove can be switched on or off. Also the heat output and the set temperature can be controlled.

Majolica sides (M-line)

Besides that Majolica ceramic panels provide a superb outlook to the stoves these majolica side panels also have a function enhancing the comfort of the stove: because of the weight of the majolica a lot of heat produced by the stove is accumulated inside the majolica tiles. This accumulated heat is released to the environment gradually. In this way the stove is still giving heat to the room even when switched off.

Week timer

The stove can be programmed for 7 days with 2 programmes.

Save mode

The stove shuts down automatically when the room temperature is 2°C above the set temperature. The unit restarts when the room temperature is 2°C below the set temperature. This system enables to save a lot of energy.

Econo mode

The stove maintains its temperature at a constant level. Every 10 minutes the stove adjusts its power, until heating setting 1 is obtained.